

Gasoline Generator

電油發電機



SGA3001Ha
(220V/50Hz)



SGA3001Ha
(110/220V/60Hz)



SGB3001Ha
(220V/50Hz)



SGB3001Ha
(110/220V/60Hz)



SGB7001Ha
(220V/50Hz)



SGB7001Ha
(110V/220V/60Hz)



SGB7001HSa
(220V/50Hz)



SGB7001HSa
(110/220V/60Hz)

MODEL	SGA3001Ha		SGB3001Ha		SGB7001Ha		SGB7001HSa	
Frequency (Hz)	50	60	50	60	50	60	50	60
Engine								
Engine Brand	Honda							
Engine Model	GX160				GX390			
Displacement (cm ³)	163				389			
Max. Output [kW(HP)/4000m ⁻¹]	4.0(5.5)				9.6(13.0)			
Type	Air Cooled, 4-cycle, OHV Gasoline Engine							
Oil Alert System	N.A.		Standard					
Ignition System	Transistor (C.D.I.)							
Electric Start	N.A.						Standard	
Generator								
Alternator	Self-Exciting, 2-Pole, Field Rotating Type, Single Phase							
Voltage Regulator	AVR							
Phase	Single							
AC Max. Output (kVA)	2.2	2.8	2.2	2.8	5.5	7.2	5.5	7.2
AC Rated Output (kVA)	2.0	2.4	2.0	2.4	5.0	6.1	5.0	6.1
Rated Voltage (V)	220	110/220	220	110/220	220	110/220	220	110/220
DC Output	N.A.		12V-8.3A (Receptacle)					
Rated Power Factor	1cosØ							
Other Features								
Pilot Lamp	Standard (except SGA3001Ha,110/220V,60Hz model)							
Volt Meter	N.A.		Standard					
Fuel Tank Capacity (l)	3.6		16		25			
Continuous Operating Hours (hr: 100% load)	3.5	3.0	14.1	12.1	9.0	7.6	9.0	7.6
Masurement								
Dimensions (mm/LxWxH)	545x410x405		595x414x501		684x534x515		684x534x515	
Dry Weight (kg)	35.0		45.8		82.0		85.0	
20Ft Container Load	270		180		128			

*Specifications are subject to change without notice.