

with combustion engine

HDS 801 B



Mobile hot water high-pressure cleaner with combustion motor for the universal use where no power supply is available.

Standard accessories:

- Trigger gun extended
- High-pressure hose 10 m
- Spray lance 550 mm
- Triple nozzle (0°/25°/40°)
- Cage frame
- Anti-twist system (AVS)
- Sturdy tubular steel frame for handling with crane



Order no.: 1.210-101.0

Technical data

| | |
|-----------------------------------|------------------|
| Pressure (bar/MPa) | 140/14 |
| Water flow rate (l/h) | 600 |
| Max. temperature (°C) | max. 98 |
| Consumption fuel oil (kg/h) | 3.7 |
| Engine type | GX 160 K1/petrol |
| Engine manufacturer | Honda |
| Engine performance, net. (kW) | 3.6 |
| Engine performance, gross (kW/hp) | 4/5.5 |
| Weight (kg) | 110 |
| Dimensions (L x W x H) (mm) | 1168x862x767 |

with combustion engine

HDS 801 B



Details

Description

Engine and pump are installed on anti-vibration mounts in a sturdy, easily transported tubular steel frame for reliable protection against damage. Frame is powder coated to protect it against corrosion and has accessory holders to accommodate the standard accessories. Two large diametered air tyred wheels and a castor with a brake ensure convenient mobility and easy transportation.

Durable, fully enclosed three-piston axial pump with swashplate drive ensures outstanding efficiency and an extra long wear life.

Safety features like the oil deficiency protection, safety valves, water deficiency protection and the fuel deficiency protection ensure the constant availability of the unit during the tough daily use. The integrated fuel tank can be filled easily and enables long operating times. Detergents can be added to the high-pressure stream with an infinitely variable valve.

Application

Mobile unit which operates independent of electricity

For building contractors

For farmers and the forestry industry

For and local governments

Features & Benefits

Drive:

Air-cooled 5.5 PS OHV - HONDA commercial engine, pull cord start

Robust, powerfull, self-sufficient mobility

High-pressure pump:

Brass cylinder head with suction and pressure valves from high-grade steel

Long service life, allows use of a wide range of detergents, long service life, overload protection

Boiler and burner system:

High performance burner with permanent ignition, vertical heating coil

Even heat distribution, no corrosion due to condensation, emission values are lower than the standards, no risk of explosions

Safety and control equipment:

Oil deficiency cut-out

Reliable engine protection by automatic cut-out when oil level is lo

Water deficiency cut-out

with combustion engine

HDS 801 B



Burner is automatically switched off when water supply is low, protection against overheating

Miscellaneous:

Sturdy tube frame chassis, powder coated, 2 big air filled wheels, 1 castor with built-in brake, 2 ergonomic handles

Overall protection to avoid damage, easy to move, safe parking, corrosion resistant

Accessory holders and nozzle holder on the frame chassis

Accessories are always at hand and tidy, safe storing of the triple nozzle and Dirt Blaster

Large removable fuel tank

Long operating times, easy to fill

with combustion engine

HDS 801 B



Accessories

Adapter

Adapter M22 - Swivel

M22 x 1,5 female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.

Order no. 4.424-004.0



Angular spray lance

WC and gutter lance

Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.

Order no. 4.760-073.0



Automatic, self-winding hose reels

Hose reel, automatic, 20 m, painted

Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.

Order no. 2.639-919.0



Swivel holder

Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.

Order no. 2.639-931.0



Hose reel, automatic, 20 m, stainless steel

Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.

Order no. 6.391-421.0



with combustion engine

HDS 801 B



Automatic, self-winding hose reels

ABS hose reel stainless steel

High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprung drive. Connection for HP hoses with nipple.

Order no. 2.641-866.0



ABS wall fastening stainless steel

Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.

Order no. 2.641-867.0



Backflow check valve

Backflow preventer

To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection

Order no. 2.641-374.0



Boron carbide nozzle

Boron carbide nozzle, for machines as of 1000 l/h

In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

Order no. 6.415-084.0



Connector

Nozzle connector/screw connector

Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.

Order no. 4.402-022.0



with combustion engine

HDS 801 B



Coupling

Double connector

Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.

Order no. 4.403-002.0



Cup foam lance

Cup foam lance

Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.

Order no. 6.394-668.0



Tank 1L

Order no. 6.414-954.0



Dirt blaster - changeover to fan jet

Dirt blaster - changeover to fan jet

Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Changeover to high-pressure fan jet max. 300 bar/30 MPa, 85 °C

Order no. 4.763-956.0



Dirt blaster – changeover to low pressure cleaning agent intake

Dirt blaster - changeover to low pressure cleaning agent intake

Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Changeover to detergent intake (low pressure) max. 300 bar/30 MPa, 85 °C

Order no. 4.763-950.0



with combustion engine

HDS 801 B



Dirt blaster – non-changeover

Dirt blaster - without changeover function

The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.

Order no. 4.763-252.0



Doppelstrahlrohr

Double lance 960 mm

960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).

Order no. 6.394-665.0



Easy Foam Set

Easy Foam Set with RM injector

HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.

Order no. 2.640-691.0



Easy Press high-pressure gun with holding power reduction (Kärcher patent)

Extended easy press trigger gun

Extended easy press high-pressure trigger gun for high-pressure hoses with rotating connector.

Order no. 4.775-529.0



with combustion engine

HDS 801 B



Fine-mesh water filter

Fine-mesh water filter, 100 µm, R 3/4"

Fine-mesh water filter, 100 µm, max. temperature 60°C. Protects the high-pressure cleaner from dirt particles contained in the water. Transparent filter cup. Water flow rate up to 1200 l/h. Connector 3/4".

Order no. 2.637-691.0



Fine-mesh water filter with adapter

Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".

Order no. 4.730-102.0



Flexible spray lance

Flexible lance 1050 mm

1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.

Order no. 6.394-654.0



Foam nozzle mounting kit

Foam nozzle kit

Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

Order no. 2.637-926.0



Geka coupling

Geka coupling with hose liner, R 1/2"

with hose liner

Order no. 6.388-461.0



with combustion engine

HDS 801 B



Geka coupling

Geka coupling with hose liner, R 3/4"

with hose liner

Order no. 6.388-455.0



Geka coupling with female thread, R 3/4"

with female thread

Order no. 6.388-473.0



Hard surface cleaner FR 30 ME

FR 30 ME surface cleaner

Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.

Order no. 2.640-355.0



Hard surface cleaner FRV 30

FR Venturion

With the integrated, automatic suction of the waste water the FRV 30 allows more efficient surface cleaning for indoor and outdoor usage. The inconvenient flushing of the surface after cleaning is not necessary anymore because the waste water can be drained off well-directed through the included 5m suction hose. Non-marking wheels and ceramic bearings are further quality features. Machine specific nozzle kit has to be ordered separately. Max. 250 bar / 1000 l/h / 60°C.

Order no. 2.642-169.0



Nozzle kit 040 - for FRV 30

Kärcher FRV 30 nozzle kit includes power nozzles and venturi nozzle for optimal cleaning performance. Special fitting tool included.

Order no. 2.642-431.0



with combustion engine

HDS 801 B



Hard surface cleaner FRV 30

Extension hose 5 m

5m extension hose for FRV 30. Connection sleeve included.

Order no. 4.440-939.0



HKF 50 spray head, brass

HKF 50 spray head , brass

Depth of immersion 850 mm. Interior cleaning head for barrels and containers with bungholes of 50 mm and more. Can be directly connected to the high-pressure cleaner. Electric motor drive. Operation is possible both vertically and horizontally



Order no. 3.631-039.0

Hose reel add-on kit

Hose reel kit for HDS 801/1050 B/D

ABS hose reel for mounting on the machine. For safe and tidy stowage of high-pressure hoses (with connecting hose to machine's HP outlet). Can be rotated under pressure, with M 22 x 1.5 connection.



Order no. 2.637-733.0

HP detergent injector

Detergent injector for high pressure

Cleaning agent dosage at high pressure 3 - 5 %

Order no. 3.637-170.0



Detergent injector for high and low pressure (without nozzles)

Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.

Order no. 3.637-001.0



with combustion engine

HDS 801 B



HP hoses with swivel 10 mm

High-pressure hose, 10 m DN 6, AVS trigger gun connector

10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.

Order no. 6.389-853.0



High-pressure hose, 15 m DN 6, AVS trigger gun connector

15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.

Order no. 6.390-174.0



High-pressure hose, 15 m, DN 6, AVS trigger gun connection, food industry, grey

Food industry version, AVS connection in the pistol. NW 6/155 °C/250 bar

Order no. 6.390-445.0



HP nozzle spray angle 0°

High-pressure nozzle with 0° spray angle

High-pressure nozzle with powerful jet for extremely stubborn dirt.

Order no. 2.884-533.0



Longlife 400

High pressure hose DN 6, 10 m, Longlife

With patented AVS connection in the trigger gun (pivot-mounted).

Order no. 6.391-882.0



with combustion engine

HDS 801 B



Longlife 400 with unions on both sides

High-pressure hose 1.5 m, DN 8, including □ connectors

1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).

Order no. 6.390-178.0



Longlife food industry version

High-pressure hose Longlife 400, 15 m, DN 6, AVS trigger gun connection

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)

Order no. 6.391-888.0



Machine-specific nozzle kit for HSC##

Nozzle kit for surface cleaners (type-specific) 500 - 650 l/h

Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).

Order no. 2.640-401.0



Machine-specific nozzle kit with order no. 3.637-170

Machine-specific nozzle kit for order no. 3.637-170 HDS 500-700 l/h

For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union

Order no. 4.769-046.0



with combustion engine

HDS 801 B



Nozzle insert with order no. 3.637-001

Nozzle insert to order no. 3.637-001, Low pressure for machines up to 1100 l/h

For low pressure with machines up to 1.100 l/h

Order no. 4.769-001.0



Nozzle kits for Inno/Easy Foam Set

Nozzle kit 055 for Inno/Easy Set 500 - 600 l/h

Optimal adaptation to different machine outputs for economic use.

Order no. 2.640-870.0



Nozzle pack for wet blasting attachment

Nozzle kit for wet blasting attachment 040

Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.

Order no. 2.637-900.0



Pipe cleaning hose, ID 6

Pipe cleaning hose

20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).

Order no. 6.390-028.0



Pipe cleaning hose, DN 6, 30 m

30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).

Order no. 6.390-029.0



with combustion engine

HDS 801 B



Power nozzle spray angle 15°

Power nozzle 15° spray angle

Fan jet nozzle with 15° spray angle suitable for stubborn dirt.

Order no. 2.883-388.0



Power nozzle spray angle 25°

Power nozzle 25° spray angle

Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.

Order no. 2.883-805.0



Power nozzle spray angle 40°

Power nozzle 40° spray angle

Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.

Order no. 2.884-522.0



Push-on washing brush

Push-on wash brush

Push-on wash brush for double/triple nozzle. Simply push on to nozzle.

Order no. 4.762-328.0



Push-on wash brush, M 18 x 1.5

Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.

Order no. 4.762-016.0



with combustion engine

HDS 801 B



Push-on washing brush

Push-on washing brush

With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.

Order no. 4.762-497.0



Quick connect

Quick coupling

For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.

Order no. 6.401-458.0



Plug nipple

Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.

Order no. 6.401-459.0



Rinnenreiniger

Gutter cleaning lance

The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.

Order no. 2.642-305.0



Rollover nozzle holder

Rollover nozzle holder

Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle).

Order no. 4.764-012.0



with combustion engine

HDS 801 B



Rotary coupling

Rotary coupling

Reliably prevents high-pressure hose twisting. Connection M 22 x 1.5 m. protector

Order no. 4.401-076.0



Rotary coupling

Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.

Order no. 4.401-091.0



Rotating washing brush

Rotating wash brush for > 800 l/h high-pressure cleaners

The rotating wash brush driven by the water jet is suitable for > 800 l/h high-pressure cleaners; gently and effectively removes fine dust and grime from all surfaces.

Order no. 4.762-283.0



Rotating wash brush for > 800 l/h high-pressure cleaners

The rotating wash brush driven by the water jet is suitable for > 800 l/h high-pressure cleaners; gently and effectively removes fine dust and grime from all surfaces.

Order no. 4.762-287.0



Shut-off cock

Shut-off valve

Shut-off valve for ease of use and convenient control of the pipe cleaning hose via convenient on/off function. Connects to the high-pressure cleaner (M 22 x 1.6).

Order no. 4.580-160.0



with combustion engine

HDS 801 B



Special hoses

High-pressure hose, 1.5 m DN 8, connection to hose reel

Order no. 6.388-886.0



Spray lance

550 mm lance, non-rotatable

550 mm stainless steel lance. With manual coupling. Non-rotatable.

Order no. 4.760-665.0



Lance 250 mm, non-rotatable

250 mm stainless steel lance. With manual coupling. Non-rotatable.

Order no. 4.760-667.0



Suction filter

Suction filter with check valve

Brass suction filter suitable for ponds, storage tanks, etc. With check valve.

Order no. 4.730-012.0



Suction filter without non-return valve

Without non-return valve, brass

Order no. 4.730-019.0



with combustion engine

HDS 801 B



Suction filter

Water filter

Order no. 6.414-956.0



Telescopic spray lance

Telescopic jet pipe

Order no. 6.394-690.0



Trigger guns

High end high-pressure trigger gun

Robust, professional trigger gun made of food-grade and seawater resistant materials. With optimised flow for low pressure loss at water flow rates of up to 2500 l/h.

Order no. 4.775-823.0



Triple nozzle, touchless changeover

Triple nozzle, touchless changeover

Triple nozzle with high-pressure pencil jet, high pressure fan jet (25°) with power nozzle and low-pressure fan jet (40°). Fast and easy jet changeover by turning the nozzle.

Order no. 4.767-112.0



with combustion engine

HDS 801 B



Triple nozzles

Triple nozzle 038

Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.

Order no. 4.767-149.0



Water supply hose

Water supply hose

NW 13 R1" / R 3/4", up to 30 °C

Order no. 4.440-038.0



Water supply hose

NW 19 R1" / R 3/4", up to 85 °C, for pick-up

Order no. 4.440-207.0



Wet blasting attachment (without nozzle)

Wet blasting attachment with flow control (without nozzles)

Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.

Order no. 4.762-010.0



Wet blasting attachment without flow control (nozzles not included)

Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.

Order no. 4.762-022.0

